




## PRODUCT SPECIFICATION SHEET

### Specifications:

Core: Multi-Strand 0.75mm PMMA Fiber  
 Outer Jacket: Treated PVC tube  
 Outside Diameter (O.D.): 3.0mm-12.0mm  
 Spool Length: 1350m-100m  
 Bend Radius: Minimum 6 x fiber diameter  
 Acceptance Angle: 50°  
 Numeric Aperture: 0.60  
 Attenuation: ≤0.2dB/M (ESKA) or 0.3dB/M (MF)  
 Operating Temperature Range:  
 Minimum: -15°C  
 Maximum: 70°C



Ordering Code	No. of Strands	Active Diameter	Outer Diameter	Min. Bend Radius	Reel Length	Fiber Brand
MEOF-3*0.75	3pcs	1.2mm	3mm	18mm	1350m	Mitsubishi ESKA or Minar MF
MEOF-4*0.75	4pcs	1.5mm	3.5mm	20mm	900m	
MEOF-7*0.75	7pcs	2mm	4mm	25mm	900m	
MEOF-11*0.75	11pcs	2.5mm	4.5mm	28mm	450m	
MEOF-14*0.75	14pcs	3mm	5mm	30mm	450m	
MEOF-25*0.75	25pcs	4.5mm	6mm	35mm	300m	
MEOF-50*0.75	50pcs	6mm	9mm	60mm	250m	
MEOF-75*0.75	75pcs	8mm	11.5mm	105mm	200m	
MEOF-100*0.75	100pcs	9mm	12mm	110mm	100m	

### OTHER INFORMATION:

1. Customized no. of strands and outer diameter are available.
2. Foam spool is applied in the packing. Fiber cable without the foam spool is available at request.
3. When the active diameter is over 1.5mm, multi-string fiber cable is recommended over the single strands sheathed fiber cable as the multi-string has a smaller bending radius.
4. The light engine, depending on its power consumption and is capable for different length and number of the fiber cable.



## MINAR ILLUMINATION ELECTRONIC LTD.

### 佛山铭家照明电器有限公司

Add: Room 504, Building 3, Taohui Home Appliance Park, Sanle East Road 23, Shunjiang Community,  
 Beijiao Town, Shunde District, Foshan City, Guangdong Province, China

Contact: George Yenn Mobile/Wechat/Whatsapp: +86 13602260195 <http://www.minarpof.com> Email: [markets@minar.com.cn](mailto:markets@minar.com.cn)